

XOms | XOms-MT | XOps | XOps-MT

Smart Manufacturing & Packaging Solutions www. pallet-stretch-wrapping-machines.com.au Phone 1300 722 868

X0 Series


del	X0ms	X0ms-MT	X0ps	X0ps-MT
Essential Parameter	Mechanical Stretch	Mechanical Stretch+M turntable	Pre-stretch	Pre-stretch+M Turntable
	Mechanical			
Machine size (mm)	2435*1650*2424	2797*1722*2419	2435*1650*2424	2797*1722*2419
Machine weight	530KG	530KG	550KG	550KG
Machine power	1.2KW	1.2KW	1.5KW	1.5KW
Voltage	220V			
Load weight	1500KG	800KG	1500KG	800KG
Turntable speed	0-12rpm			
Packing speed	30 loads/h			
Column height	2400mm Standard (2800mm, 3200mm and 3600mm optional, not stocked made to order)			
Packing height	2000mm Standard (2400mm, 2800mm 32mm optional, not stocked, made to order)			
Turntable height	81mm			
Turntable size	1650mm Standard (1800mm / 2000mm / 2200mm / 2400mm optional, not stocked, made to order)			
Up&down speed	0-5.9m/min			
Pre-stretch rate			250%	250%
Film Width	500mm			
Film paper Core	76mm			
Fix film on pallet	Manual			
Certificate		C	E	
pearance/Craft				
Machine materials	Steel, Aluminum			
Industrial appearance	Metal plate Three Color LED - BLUE ready to run, GREEN running a cycle, RED fault dectected			
Indicator light	Three C	olor LED - BLUE ready to run, G	REEN running a cycle, RED fau	ult dectected
ontrol				
Soft start & stop	•	•	•	•
Intelligent Alarm	•	•	•	•
Stop at original	•	•	•	•
Turntable lock				•
PLC	PCB Integrated Circuit Plate			
Inverter				
Sensor switch	SICK			
Touch screen	SMART WASP			
Motor				
Safety device	Pressure sensitive safety stop to avoid crushing incidents - Safety brake makes it impossible for the wrapping head to drop			
otional Functions				
Top Pressure Function	0	0	0	0
Top Pressure Function			1001	1000
Ramp	0	0	0	0


Annotation:

With the configuration o Optional configuration


No configuration

*The parameter information is for reference only









3 Years





X0ms with new generation of mechanical resistance film carriage

1. Adjustable knob with physical feedback for the wrapping tension, is easy and convenient to adjust



film carriage

1. Use the touch screen to precisely adjusts the wrapping tension

X0ps with the latest cost-saving power pre-stretching

2. The maximum pre-stretching ratio is 250%, giving you impressive film saving







PCB control system

LED Indicator

1. Four independent chips provide the smarts to control the operation of the wrapper

2. The integrated circuit system, reduces maintenance and repair cost.

Intuitive and Easy to Operate Touch Screen 6 Memory Functions + One Button Start

1. Easy to operate clear bright touch screen that your operators will love

2. Six program memory function, make parameter setting easier with simple recall

3. Two levels of Password protection to stop those that like to play with setting

4. One button to start the wrapping cycle ensures convenient simple operation

All-in-one alloy Aluminum Column with Lifetime Warranty

1. 4000 tons extruded column, integrally formed, solid and durable

- 2. Modular assembly, easy to install
- 3. Double chain lifting system, ensures safety
- 4. LED tri-color indicator light

